



Short Communication

Volume 19 Issue 4 - October 2026  
DOI: 10.19080/OFOAJ.2026.19.556019

Oceanogr Fish Open Access J

Copyright © All rights are reserved by Cliff Dansoh

# Reinstating Historic Tidal Mill Infrastructure for Low-Head Renewable Energy Generation: Lessons from Tide Mills Creek, Newhaven, UK



Cliff Dansoh\*

*College of Creativity, Technology and Society, University of Brighton, United Kingdom*

**Submission:** September 30, 2026; **Published:** October 06, 2026

**\*Corresponding author:** Cliff Dansoh, College of Creativity, Technology and Society, University of Brighton, United Kingdom

## Abstract

Historic tidal mills once formed an important component of coastal energy infrastructure throughout the United Kingdom and Europe. Although many have fallen into disuse, remnant tidal creeks, impoundments, sluices and culverts remain. These assets present an opportunity for the deployment of modern low-head renewable energy technologies. This paper evaluates the potential for reinstating tidal impoundment at Tide Mills Creek, Newhaven, United Kingdom, using a range of low-head generation technologies. Unlike the historic tidal mill, the present-day creek is open to natural tidal exchange and does not currently impound water. The study therefore considers a reinstatement scenario in which a tidal barrier and controlled sluice system are introduced to recreate hydraulic head. Annual energy yields were estimated for Very Low Head (VLH) turbines, Hydrostatic Pressure Turbines (HPT), Archimedes Screw Turbines (AST) and breastshot waterwheels using site-specific tidal data. Results indicate that dual VLH turbines could generate approximately 104.6 MWh/year, while dual HPT systems could achieve approximately 101.9 MWh/year. The work demonstrates that abandoned tidal mill infrastructure may provide a practical pathway for coastal renewable energy generation while supporting heritage conservation, flood resilience and habitat enhancement.

**Keywords:** Tidal mills; Very-low-head hydropower; Tidal impoundment; Renewable energy; Estuarine restoration; Coastal infrastructure

## Introduction

Interest in predictable renewable energy resources has renewed attention on tidal energy technologies. While major tidal barrages and lagoons continue to face significant economic and environmental barriers, smaller-scale schemes based on existing hydraulic infrastructure may provide a more practical alternative. Historic tidal mills represent one such opportunity.

Tidal mills operated extensively around the coasts of Britain and Europe from the medieval period until the nineteenth century, using impounded tidal water to drive mechanical equipment. Many former sites retain substantial hydraulic infrastructure despite no longer being used for energy production. Reinstating these systems using modern low-head generation technologies could provide renewable electricity while preserving industrial heritage and supporting wider coastal management objectives.

Tide Mills Creek, located between Newhaven and Seaford on the south coast of England, provides an interesting case study.

The original tidal mill ceased operation during the nineteenth century and the present creek is hydraulically open to the sea. However, a substantial culvert connection between the creek and tidal waters remains. This study investigates the extent to which reinstatement of tidal impoundment could support modern low-head hydropower generation.

## Site Description

The former Tide Mills tidal mill was established during the eighteenth century and operated until approximately 1883. Today, the site consists of a tidal creek connected to the sea by a concrete culvert system ranging between approximately 1.3 m and 1.7 m in diameter.

A key distinction must be made between the historic and current conditions. The existing creek is open to natural tidal exchange and therefore does not create sufficient hydraulic head for meaningful power generation. For this reason, the energy

assessments presented here are based on a reinstatement scenario in which a low dam and sluice-gate arrangement are installed to recreate a managed tidal impoundment.

Under this concept, water is impounded during flood tides and subsequently released through energy conversion devices during ebb tides, recreating the operating principle of the original tidal mill while employing modern turbine technology (Figure 1).



**Figure 1:** Conceptual reinstatement of Tide Mills Creek incorporating dual VLH turbines (based on image prepared by Phil Nutley, [University of Brighton/ Nevermind Global Limited], reproduced with permission) and Archimedes screw turbines, together with sluice control and fish-pass provision.

## Methodology

Several low-head technologies appropriate to tidal impoundment systems were assessed:

- Very Low Head (VLH) turbines
- Hydrostatic Pressure Turbines (HPT)
- Archimedes Screw Turbines (AST)
- Breastshot waterwheels
- Vertical-axis hydrokinetic turbine concepts

The modelling utilised hourly tidal levels from the Newhaven

area and assumed operation through controlled sluice-gate management.

For VLH and HPT configurations, the creek was allowed to fill during flood tide before controlled release through the turbines on the ebb cycle. Archimedes screw systems were modelled using an ebb-generation configuration. The breastshot waterwheel was assessed as a heritage-focused alternative operating under a reduced flow regime.

Energy production was calculated from hydraulic head, discharge rate and device efficiency for a representative annual period.

## Results

**Table 1:** Estimated Annual Energy Yield.

| Technology                    | Annual Yield (MWh/year) | Principal Advantage            |
|-------------------------------|-------------------------|--------------------------------|
| VLH (2 units)                 | 104.6                   | Highest energy yield           |
| HPT (2 units)                 | 101.9                   | Effective under very low heads |
| AST (multi-screw arrangement) | 62.3                    | Fish-friendly operation        |
| VLH (1 unit)                  | 78.7                    | Lower capital cost option      |
| HPT (1 unit)                  | 62.6                    | Simple deployment              |
| Breastshot waterwheel         | 19.2                    | Heritage and educational value |
| Vertical-axis turbine         | 4.8                     | Minimal infrastructure         |

The estimated annual yields are summarised in Table 1.

The dual VLH configuration produced the highest estimated annual generation at approximately 104.6 MWh/year. The dual HPT arrangement demonstrated similar performance, producing approximately 101.9 MWh/year.

Archimedes screw systems delivered lower annual yields but remain attractive due to their proven fish-passage characteristics and established environmental acceptance. Waterwheel solutions generated substantially lower outputs but offer opportunities for heritage interpretation and tourism.

## Discussion

The results demonstrate that reinstated tidal mill infrastructure can provide useful quantities of renewable electricity using commercially available low-head technologies. Although the energy yields are modest compared with utility-scale renewable projects, they are significant at the local scale and could support visitor facilities, environmental monitoring infrastructure, educational centres, or community energy schemes.

The principal value of such schemes may extend beyond electricity generation. Reinstated tidal impoundments could contribute simultaneously to:

- a) preservation of industrial heritage
- b) coastal climate adaptation
- c) flood resilience
- d) educational and tourism opportunities
- e) habitat creation and managed estuarine restoration

The VLH and Archimedes screw technologies are especially attractive because of their relatively low rotational speeds and favourable environmental performance reported in previous studies of fish passage and aquatic ecosystem interactions.

The Tide Mills concept also has wider applicability. Numerous former tidal mill sites remain distributed around the coasts of the United Kingdom, France, Portugal and the Netherlands. Many retain impoundments, sluices, culverts or embankments that could potentially support modern low-head renewable energy systems with minimal civil-engineering intervention [1-7].

## Conclusion

This study investigated the feasibility of reinstating a historic tidal mill system at Tide Mills Creek, Newhaven, for renewable

electricity generation.

Key findings include:

- a) The existing creek is open to natural tidal flow and does not currently function as a tidal mill.
- b) Reinstatement of tidal impoundment through sluice-control infrastructure could enable modern very low-head (VLH) hydropower generation.
- c) Dual VLH turbines provided the highest modelled energy output (104.6 MWh/year).
- d) Dual HPT systems achieved comparable performance (101.9 MWh/year).
- e) Archimedes screw systems offered lower yields but potentially superior environmental compatibility.
- f) Historic tidal mill infrastructure may provide a practical mechanism for combining renewable energy generation, heritage conservation and coastal resilience.

Future work should include detailed hydraulic modelling, environmental assessment, ecological studies and techno-economic evaluation before implementation.

## References

1. Angeloudis A, Falconer RA, Bray S, Ahmadian R (2016) Representation and operation of tidal energy impoundments in coastal hydrodynamic models. *Renewable Energy* 99: 1103-1115.
2. Quaranta E, Bahereni A, Riasi A, Revelli R (2022) The Very Low Head Turbine for hydropower applications in existing hydraulic infrastructures. *Sustainable Energy Technologies and Assessments* 51: 101924.
3. Roome E, Robins P, Ahmadian R, Austin M, Hanousek N, et al. (2024) Assessing hydrodynamic impacts of tidal range energy impoundments in UK coastal waters. *Renewable Energy* 237: 121601.
4. Waters SR (2015) Analysing the performance of the Archimedes screw turbine within tidal range technologies. MSc Thesis, Lancaster University.
5. Wolter C, Müller G (2004) The breastshot waterwheel: design and model tests. *Proceedings of the Institution of Civil Engineers: Engineering Sustainability* 157(4): 203-211.
6. Historic England (2018) Mills: Introductions to Heritage Assets. London: Historic England.
7. The Tide Mills Project (2026) History of Tide Mills and the former tidal mill complex.



This work is licensed under Creative Commons Attribution 4.0 License  
DOI: [10.19080/OFOAJ.2026.19.556019](https://doi.org/10.19080/OFOAJ.2026.19.556019)

**Your next submission with Juniper Publishers  
will reach you the below assets**

- Quality Editorial service
- Swift Peer Review
- Reprints availability
- E-prints Service
- Manuscript Podcast for convenient understanding
- Global attainment for your research
- Manuscript accessibility in different formats  
( Pdf, E-pub, Full Text, Audio)
- Unceasing customer service

**Track the below URL for one-step submission**  
<https://juniperpublishers.com/online-submission.php>