

# Intellectual Irrigation Management in Mining Frozen Farming in Azerbaijan



**RAE ZH Aliyev\***

*Institute of Soil Science and Agrochemistry of NAS of Azerbaijan*

**Submission:** March 06, 2018; **Published:** April 09, 2018

**\*Corresponding author:** RAE ZH Aliyev, Institute of Soil Science and Agrochemistry of NAS of Azerbaijan, Email: [zakirakademik@mail.ru](mailto:zakirakademik@mail.ru)

## Abstract

This article examines the current state of soil and water resources, farmland t.ch.i Azerbaijan Republic, the problem of progressive water and wind soil degradation, the need for the organization of agriculture, taking into account the introduction of automated control systems for irrigation using water saving technology and hardware equipment in it, the study of the characteristics and analysis of experience implementing measures to stabilize ecological and drainage system of agriculture in conditions of insufficient moisture areas in the country, as well as basic aspects of development of environmental reclamation approach balanced, rational use of a particular system of crop rotation and crop taking into account the requirements of economic development and environmental management.

**Keywords:** Irrigation; Technology; Degradation; Automated management of low-intensity zones; Agriculture

**Abbreviations:** CC: Communications Controller; TP: Transform Point; HB: Humidity BETA; DB: Data Base

## Introduction

The main directions of economic and social development of the Republic is the characteristic intensify agricultural production. A powerful tool for the intensification of agricultural production in the face of his specialization is irrigation. In areas of insufficient moistening (especially typical for mountainous areas) irrigation is one of the decisive factors of the cultivation of high and stable yields of agricultural crops.

### The purpose of the study

For this purpose, requires the development of new technical solutions and the introduction of automated systems of low irrigation of crops eligible for Ecology and environment Wednesday to improve their environmental condition of irrigated lands, reduce water consumption per unit products and increase the productivity of those or other crops on irrigated field.

### Research methods and moves the discussion

Irrigated soil in Azerbaijan covers 1.45 thousand hectares. It is believed that factors directly affecting the fascination with crop yields and productivity in this area per hectare of arable land and agricultural land at minimal cost, labor and funds also apply automation application.

Automated irrigation increases the effectiveness of all factors intensifying: Chemistry, integrated mechanization, intensive technology upgrade, etc. It allows you to create a large zone of guaranteed crop production.

### Objects of study

The object of the study is to explore and create the correct methods for regulating water use and supply of plants by means of irrigation in regardless of weather conditions. To this end, we have developed and introduced into production design systems of automated management systems for irrigation of low- Micro-tailings of self-oscillating action action, successfully passing the resource tested test on vydelochnyh soils under Orchard, Lip-Hachmasskoj area on the foothills of the Mountain above level at an altitude of 600 metres sea with sloping terrain 0.02. (see the concept of impulse systems rain avtokolebatelnogo actions with automated controls.

Construction and functional description of the CMO AY so for operational control of the weather conditions in the region needed to meet the challenges of planning and operational irrigation management crop fields at the local gidrometeopunkte are set measurement sensors with probes for telemetric measurement taking the readings the main parameters:

- Wind speed-V analog signal (Titus) with period recording of parameter values in the cycle of 30minutes.
- Air temperature-tv, analog signal (Titus) with period recording of parameter values in the cycle 30min. in) humidity-Wb, analog signal (Titus) with period recording of parameter values in the cycle of 30 minutes.

c. The reading parameter values in the telemetricheskom code is done smart object controller (to) established in paragraph transformer via a radio channel which communicates with sensors-converters.

Ko otschitannye telemetry signals codes undergo preliminary processing, homogenization and written to main memory, which stores prior to their taking the readings the Communications Controller (CC) that is installed in the premises of the operational control technology process (ASMO)-operator. For monitoring and control of electricity supply facilities and power consumption accounting to ASMO Transform Point (TP) (see structural concept of APCS for irrigation) installed transmitters:

- a. Voltage measuring input) in TP-U (analog signal (Titus);
- b. Measurement load consumers-I U (analog signal (Titus);
- c. Electricity metering)-Wh (discrete signal integrated-TII);
- d. Control switch settings (enable-disable consumers)-SS (discrete signal position SHH).

Report parameter values in the telemetricheskom code is performed by intelligent object controller (KO) of local wire and after their initial processing and averaging is written into RAM. For monitoring and control technological process of abstraction, clarifiers (wastewater treatment plant) and pumping stations (devices increase the water pressure in the pipes) installed transmitters listed in structurally-functional schema:

- a. Water turbidity in the ponds-m (analog signal loop to read Titus, 30min);
- b. Water level in chambers-ponds-n (analog signal TITUS, read in a loop 30min) in water pressure-r installed on discharge pumps, modular and distribution reservoirs (analog signal TITUS, read in a loop 30 min);

Load dimensions electric motors-I (analog signal TITUS, read in a loop 30min);

- a. Provisions of valves-PZ (discrete signal SHH, readable in cycle 1);
- b. Power switches) Regulations-VP (discrete signal SHH, readable in cycle 1);
- c. Alarms-AU (discrete signal TCA, readable in cycle 1 with priority);

Water metering pumps and supplied in the distribution pipeline-Q (integrated signal TII, processed in the cycle of

1:00).

Soil monitoring and process control of irrigation is carried out according to the specific fields of irrigation based on measurements of the agro physical and technological parameter sensors-converters: and soil moisture) VLP-(analog signal TITUS with a 30min cycle);

- a. Evaporation from soil surfaces-Exec (analog signal TITUS with a 30min cycle); soil temperature) t°-(analog signal TITUS with a 30min cycle);
- b. Water consumption irrigation on distribution pipeline plot-Q-(integrated signal with a 30min cycle);
- c. Inclusion of the GKS-discrete signal readable in a cycle of 30s;
- d. Position switching valves-(discrete signal read-SHH 30c).

Report telemetricheskom signal code is performed by intelligent object field radio communications controller and after their initial processing and averaging processor is written into RAM.

### **Enter operational data into the computer and the formation of a database (ODB)**

Recorded in the memory controller objects (to) data are programmatically by radio and wire Communications Controller (CC) connected to your computer Tower (PD) (see circuit diagram system intensity of irrigation and automated controls), according to the specified rules and written in his memory in the structure of the telemetry files (see information provision).

Computer exchange programs plays the data from RAM to the COP, trans code them and writes into the database from which displays them in real time on the display mnemoshemah, and after linearized and averaging the data on their codes programmatically are recorded in the cumulative base structure which provides information, and this generates a data bank complex tasks ASMO [1].

### **Information flows of the Automated System of low-level (ASMO)**

Before writing to the Bank data stream measurement data analyzed by specified algorithms and when the results of the analysis, with deviations from the values specified in the rules of the installations is operational control (OBU) process. Operating base control programmatically at the specified in the rules of the cycle is counted by the management module on technology directions and if there are deviations in the data records for this activity generates a control signal to the appropriate the executive body.

## Organization of the collection and transmission of data on the Internet channels

### Conditions for organization of data exchange

#### Data Interchange on the work of the system of irrigation is carried out via the Internet

To do this, you must connect through a computer modem to the telephone network and earn the right to Internet access through an Internet service provider. This requirement applies to each Subscriber. If these conditions are met, the computer 'The Center can communicate with computers on the sections of the irrigation districts of Azerbaijan and other States is the site irrigation system, where visitors will see: the latest system state data, interactive pages, created by PHP technology, rapid exchange of data and messages in real time.

Using Skype 3 users can talk on the phone and when using cameras to see each other, and when streaming video programs-view the status of the site. When measurements of parameters, it is necessary to take into account the dispersion of available measured values. The value of the parameter, which can be taken for the actual probability of 0.8, is determined by the number of repetitions of measurements is defined by the formula.

$$n_{0.8e,x} = 1.64 * 0.001(SIG_{(B)}) * ((W(HB)/10 * h)^2) + 2.27 \quad (1)$$

Where,

$n = 0.8$

(Tr)-number of retries, the measurements meet the probability 0.8;

m-0.8 (tr)-measurement accuracy (mm)

SB-standard error of measurement %

b (HB) W (HB)-moisture reserves, mm

When humidity b (HB) in the control layer (h) (a), m.

### The source (start) Measurement of soil moisture and the calculation of the initial moisture reserves in the soil W0

**General description of the task:** Original moisture reserves W0 soil in the active layer defined by the formula:

$$dWHB = W(\tau) - W(HB) \quad (2)$$

Where,

h (a) is an active soil layer, m (it is assumed that the active layer of the soil is divided into layers of 0.20m -0.30)

$\gamma$  is the average density of soil layer, t/m<sup>3</sup> entry in program code-gamma\_sr.

$\beta\tau$ -soil moisture at field station in% to mass of dry soil in the program code recording the moment-(Veta\_tau). For automated definition starting soil moisture reserves come from the fact that the value (Veta\_tau) is defined  $\beta\tau$  measure humidity, it is installed on a stretch of fields on n0, 8 (tr) measurements (write in code, n\_0 8 ex).

The measured values are automatically written to the parameter file DataPar.dbf data bank on N\_code element parameter belongs (see. (c) special section 'Dataware >>') [2]. To specify the conditions for the calculation of the value of the conditionally required variables are written in the job (see. ZADANIE\_3 information).

Defining the value of starting (the original) soil moisture deficit is determined programmatically moisture reserves and necessary rules. Results of solution of the problem is written to the output document DOC\_3 and plotted on the graph.

Description of the algorithm in accordance with the task of determining soil moisture and moisture reserves on a plot of field irrigation (see information provision 'ZADANIE\_3'). Searching for values from the database (from the section information management): -parameter values automatically read from a file DataPar.dbf on N\_code element parameter belongs; -the value of the N\_code element is read from the file ELEM. Dbf on key: SL\_SYST + SSYST + SL\_MODYLE + SL\_GROUP + SL\_VID + SL\_TYPE.

Formation of a look up key for N\_code (see instructions to the operator) and select SL\_SYST.dbf) from a file system to which the parameter element.

b) from file SL\_SSYST.dbf to select subsystem.

in) from a file + SL\_MODYLE.-module dbf.

g) from the file SL\_GROUP.dbf-the group to which an item belongs measured parameter.

d) from the file SL\_VID.dbf-element kind of measured parameter.

(e) of the file item type TYPE.dbf SL\_ measured parameter.

f) NAME is the NAME of the element is entered from the keyboard;

If the elements identified by coupling multiple (see. ZADANIE\_3, write

4), then each of them is assigned a position number.

The item number is appended to the name through the separator [\_]-(NAME\_1 >). For formed coupling is TLS\_X. dbfN\_ code.

From DataPar.dbf to N\_code + Zdate and <PARAM> parameter name in ZADANIE\_3 (+) programmatically is its ZNACH value for each field.

i. The obtained values of parameters-moisture content at the specified date, or BETA\_tau stocks of moisture on the specified date W (tau) for each section of a field are written to the output DOC. 3 see layouts output documents 'Supply of moisture on irrigation fields >> After identifying the BETA\_tau moisture or soil moisture reserve W (tau) is defined or moisture deficit soil moisture reserve [2-4].

ii. Determination of moisture deficit soil moisture reserves and to stretch the field and if the software is determined by ZADANIE\_3) humidity and BETA\_tau of DataPar.dbf found its importance, relatively humidity moisture deficit lowest water consumption BETA\_ (HB) is: [5-7].

$$dBETA\_HB = BETA\_ (HB) - BETA\_tau \quad (3)$$

Where,

BETA\_ (HB)- from SF\_Plot.dbf and ConSoil.dbf; BETA\_tau- from the 4.2.3.

Moisture deficit values are automatically written to the output DOC dokumnt. 3

b) If for ZADANIE\_3 is determined by the supply of moisture in soil W (tau) and of DataPar.dbf found its value, reserve moisture deficit moisture while the smallest capacity dW (HB) is equal to:

$$DW (HB) = W (tau) - W (HB) \quad (4)$$

Where is

W (HB)-from SF\_Plot . dbf and

ConSoil.dbf; W\_tau-from the 4.2.3

After identifying data for each of the specified sites field is determined; and average value) BETA\_AV humidity and soil moisture reserves generally W\_AV on the field:

$$BETA\_AV = 1/n \sum (BETA\_tau) \quad (5)$$

Where is

n is the number of balanced plots involved per- from ZADANIE\_3, 4 entry;

(BETA\_tau )i -soil moisture is relatively dry soil from 4.2.1 for each plot.

b) if defined (W\_tau), the average soil moisture reserve the entire field

$$dBETA\_AV = 1/n * \sum (dBETA\_tau) I \quad (6)$$

g) the average value stock deficit soil moisture fields:

$$dW\_AV = 1/n \sum (dW\_AW) I \quad (7)$$

Calculated values in clause 4.2.3 a),),) are automatically written to the string < averaging field ... .. >.

d) Defined e in items 4.5 and 6 DOC. 3 bar chart displays the parameter values 'supply of moisture on the field irrigation>>

e) after seeing the DOC. 3 prompted < Will solve the problem for other fields on this date >. <Да>, <Нет>. When you type <Да> < message, type the name of the field and economy in ZADANIE\_3 > ZADANIE and displayed for data entry.

4.2.4 If the database parameter value specified in ZADANIE\_3, it displays an < Value specified in the ZADANIE parameters in the database are missing. Will measure these parameters?. <Да>, <Нет>. If <Да> then go to

4.2.1. If <Нет>, then the solution of the problem of consummated and exit the menu.

4.2.5 before starting measurements determines the number of dimensions at each site provides the probability computed value not less than 0.8 at minimum cost of labour on measuring n\_0, 8Ex:

$$n\_0, 8Ex: = 1, 64 * 0.001 (SIG\_B) * (W (HB)/10 * h) * 2)) + 2.27 \quad (8)$$

Where is:

SIG\_B-set the value of the standard error in percent; Beta (HB)-from ZADANIE\_3;-W (HB)-supply of moisture in the soil, in mm when Humidity BETA(HB) of the SF\_Plot.dbf;-h is the depth of the soil layer (mm), which should be dimension.

4.2.6 Perform n\_0, 8Ex measurements specified ZADANIE\_3 parameter, row 2 on each site and write to DataPar.dbf to N\_code, Zdate, Ztime.

4.2.7. Calculate the mean value of the measurements of (make a selection from DataPar.dbf to N\_code + Zdate.

Average soil moisture reserve W\_AV is equal to:

$$W\_AV = 1/n\_0, 8Ex * \sum (W\_0, 8Ex) i (mm) \quad (9)$$

Where,

W\_0.8 Ex -the value of the stock of moisture each dimension selected in item 4.2.6 (If measured soil moisture BETA\_0, 8Ex, the average humidity BETA\_AVas well:

$$BETA\_AV = 1/n\_0, 8Ex * \sum (BETA\_0, 8) i (%) \quad (10)$$

Where is

BETA\_0, 8 Ex-the value soil moisture for each measurement computed values to assign:

a) W\_AV: = W (tau);

b) VETA\_AV: = BETA\_tau and write to output DOC. 3 as in 4.2.1 and 4.2.2 as; 4.2.3.


4.2.8 Filled DOC. 3 is written to the folder that you want to send through the channels of the Internet. Programme codes are shown in a separate annex.

### Conclusion

The study identified possible operational solving complex problems of an operational definition of soil-conservation settings.

### References

1. Aliev BH, Aliev ZH (2001) Zoning of the territory of Azerbaijan Republic on choosing advanced irrigation techniques. Monograph, Publishing house "Ziya". Baku, Azerbaijan pp. 297.
2. Aliev BH, Aliev ZH (2003) Irrigated agriculture in the mountain and foothill regions of Azerbaijan. Monograph Publishing house "Naji Zia EPG Ltd" Baku, Azerbaijan pp. 330.
3. Aliev BH, Aliev ZH (1999) Techniques and technology few intensive irrigations in condition of the mountain region of Azerbaijan. Publishers "Elm", Baku, Azerbaijan pp. 220.
4. Aliev ZH (2007) The premises about the most important problem of the agriculture in water resource provision mountain and foothill regions of Azerbaijan, //j. AAS, # 1-3, Baku, Azerbaijan pp. 179-182.
5. Aliev ZH (1999) The premises of the decision of the problems moisture provides agriculture cultures production in mountain and foothill region of Azerbaijan. The works of SRI "Erosions and Irrigations. Baku, Azerbaijan, pp. 125-129.
6. Mezhdunarodny (2002) Center C/X Research in the dry in the Dry Areas (ICARDA) Irrigation regime and monitoring equipment. Edited u. Umarova and a. Karimov. Taraz: IC "AQUA", pp. 128.
7. Nosenko RB Irrigation in the mountains. Publishing House "Kolos" Moscow, Russia 198: 143.



This work is licensed under Creative Commons Attribution 4.0 License

### Your next submission with Juniper Publishers will reach you the below assets

- Quality Editorial service
- Swift Peer Review
- Reprints availability
- E-prints Service
- Manuscript Podcast for convenient understanding
- Global attainment for your research
- Manuscript accessibility in different formats  
( Pdf, E-pub, Full Text, Audio)
- Unceasing customer service

Track the below URL for one-step submission  
<https://juniperpublishers.com/online-submission.php>